
Seating » Benches



Collection: Connect

Designed by: Botton + Gardiner




Seating » Benches


Hardwood Blackbutt	Core Powder-Coat	Core Powder-Coat	Core Powder-Coat	Core Powder-Coat
UV-Resistant Oil	White Satin	Black Satin	Charcoal Satin	Palladium Silver Satin
Core Powder-Coat	Core Powder-Coat	Solid Powder-Coat	Solid Powder-Coat	Solid Powder-Coat
Matt Black Matt	Pearl White Gloss	Coffee Satin	Cove Satin	Monument Matt
Solid Powder-Coat Medium Bronze Kinetic Flat	Textured Powder- Coat Core Ten Textured Metallic	Textured Powder- Coat Asteroid Textured Metallic	Textured Powder- Coat Bass Textured Metallic	Textured Powder- Coat Textura Black
Textured Powder- Coat Textura Monument	Textured Powder- Coat Textura White	Signature Powder- Coat Deep Ocean Satin	Signature Powder- Coat Wedgewood Satin	Signature Powder- Coat Mangrove Satin
Signature Powder- Coat Territory Red Satin	Signature Powder- Coat Claypot Satin	Signature Powder- Coat Paperbark Satin	Bold Powder-Coat Bondi Blue Gloss	Bold Powder-Coat Leaf Satin



PUBLIC SPACE FURNITURE

Seating » Benches






Seating » Benches

Modern, modular, circular bench seating in a large tall size with Blackbutt hardwood battens and a steel frame available in 27 powder-coat colours.

Description	Connect circle large tall modular bench seating is versatile, durable, and sustainable, making it suitable for a wide range of outdoor or indoor spaces. It connects with the Connect circle interlock large low to create a tiered seating design. These can be grouped with the range of 18 seating modules, consisting of geometric shapes, and interlocking elements that can transform any public space into a social hub.
	Choose from circular or oblong seating designs with integrated urban planters and tiered heights to create simple to complex configurations. Designed in-house and made locally, Connect features certified Blackbutt hardwood battens with bullnose edging and a steel frame in 27 VOC-free powder-coat colours that can be customised to suit your project.
Made In	Australia
Dimensions	Ø2450mmW x 700mmH Hardwood battens: 140mmW x 42mm thickness Spacing: 5mm gap between battens
Batten Type	Class 1 + Select Grade Hardwood: Blackbutt with bullnose edging
Frame	Powder-coated, pre-galvanised steel
Powder Coat	Core White (satin), Black (satin), Charcoal (satin), Palladium Silver (satin), Matt Black (matt), Pearl White (gloss)
	Solid Coffee (satin), Cove (satin), Monument (matt), Medium Bronze Kinetic (flat)
	Textured Core Ten (textured metallic), Asteroid (textured metallic), Bass (textured metallic), Textura Black (textured), Textura Monument (textured), Textura White (textured)
	Signature Deep Ocean (satin), Wedgewood (satin), Mangrove (satin), Territory Red (matt), Claypot (satin), Paperbark (satin)
	Bold Bondi Blue (gloss), Leaf (satin), Sensation (gloss), Lobster (satin), Moonlight (satin)

Seating » Benches

Sustainability	Certified Hardwood Blackbutt is locally sourced and certified by the Program for the Endorsement of Forest Certification (PEFC), the world's largest forestry certification system.	
	Recycled Materials We locally source our steel. It means we know it uses recycled content and is 100% recyclable.	
	Low Pollutants Our powder-coating process doesn't emit Volatile Organic Compounds (VOCs) and has Environmental Product Declarations (EPDs).	
Warranty	5-year warranty. View the <u>warranty</u> for more details.	
Lead Time	6-8 weeks	
Assembly & Delivery	Shipped fully assembled on pallets.	
Fixing Detail	Fixed by others. Fix direct to a concrete slab or through pavers and into a concrete slab.	
How to Specify	Select your batten finish Select your frame finish	



Seating » Benches

Care Instructions	<u>Hardwood</u> Cleaning Remove any loose surface deposits with a soft bristled brush and wipe down with fresh water and a non-abrasive cloth.
	Oiling Oiling of timber will postpone natural greying, repel moisture, improve mould resistance, help maintain a smooth surface texture and enhance the grain and colour.
	To maintain, lightly sand rough areas of timber and brush on one coat of timber decking oil every 6 months or as required.
	<u>Powder-Coat</u> Cleaning Carefully remove any loose surface deposits with a wet sponge or soft bristled brush.
	Use a soft (non-abrasive) cloth or brush and a diluted solution of mild detergent and warm water.
	Ensure surfaces are thoroughly rinsed with clean fresh water after cleaning to remove all residues.
	Never use thinners, abrasive cleaning agents, alcohol-based, acid or alkali cleaning agents.
Additional Comments	Hardwood is treated with a UV-resistant oil finish. Integrated lighting and power on request.

