

PROSPECT REMOVABLE BOLLARD

Accessories » Bollards



Collection: **Prospect**

Designed by: **Botton + Gardiner**

PROSPECT REMOVABLE BOLLARD

Accessories » Bollards



Hot-Dip Galvanised
Steel



PROSPECT REMOVABLE BOLLARD

Accessories » Bollards

Simple, robust removable bollard made from a standard steel “I” beam, with a circular opening for a barrier chain or cable. Galvanised finish.

Description	Featuring striking asymmetrical forms and robust materials that are based on our competition-winning designs for the Western Sydney Parklands Trust, the Prospect removable bollard is ideal for parkland and urban environments. Made from a standard steel “I” beam and available in a galvanised finish, the bollard design features folded edge details and a circular opening for a barrier chain or cable. It is secured to the base plate with a padlock and may be removed to allow vehicular access. Highly functional, the simple, robust removable bollard complements and sits within many public spaces to create a protective or architectural perimeter.
Made In	Australia
Dimensions	280Wmm x 170mmD x 820mmH 115mm high when folded
Frame	Hot-dip galvanised steel
Sustainability	Recycled Materials We locally source our steel. It means we know it uses recycled content and is 100% recyclable.
Warranty	5-year warranty. View the warranty for more details.
Lead Time	4-6 weeks
Assembly & Delivery	Removable bollard secured to base plate via padlock (padlock by others).
Fixing Detail	Base plate surface fixed by others. Anchors not included.
How to Specify	Select your product

PROSPECT REMOVABLE BOLLARD

Accessories » Bollards

Care Instructions

Hot-Dip Galvanised Steel

For general cleaning of bulk contaminants such as dirt and the like, ordinary laundry soaps can be satisfactorily used.

For more stubborn or larger areas, the use of a low-pressure wash (eg. a gurney gun) with just pure water or in conjunction with proprietary cleaning materials, such as car wash or truck wash, can be effective. It is important that the steel be washed down with fresh water after cleaning.

The cleaning treatment of the galvanising should be conservative at first and then if the situation demands, the treatment can become steadily more aggressive. Also, wherever some form of mechanical abrasion or “scrubbing” is required, the use of a hard, plastic bristle brush is recommended. Steel bristle brushes are not to be used since they will cause discolouration.

Mechanical methods of cleaning zinc surfaces can cause aesthetic issues. The “cleaned” areas are likely to contrast with adjacent untreated surfaces and may take a significant period of time to weather to a uniform colour. If aesthetics is a large concern, it is advisable to first test the cleaning method in an inconspicuous area in case the aesthetic effect is unappealing.

Additional Comments

The Prospect removeable bollard is secured to the base plate with a padlock (not included) and may be removed to allow vehicular access.

Optional plastic orange reflectors to increase visibility.
